

HONEYWELL A300 SERIES SAFETY EYEWEAR

COMFORTABLE, SAFE AND
COST-EFFECTIVE SOLUTION
FOR EYE PROTECTION



HONEYWELL A300 SPECTACLES

TECHNICAL SPECIFICATIONS		TECHNICAL SPECIFICATIONS	
Lens overall width	144.8mm	Ind. Product dimensions	5 x 14.5 x 4.4 cm
Hinge to hinge	133.3 mm	Ind. poly-bag dimensions	22.4 x 10.2 cm
Temple length	120mm	Primary Carton dimensions	30.5 x 17.8 x 10.2 cm
Lens Thickness	2.42mm	Primary Carton weight	724 Gram
Lens material	Polycarbonate	Primary Packaging QTY	20 Units
Temple material	Polycarbonate	Master Carton dimensions	61.5 x 36.8 x 54.6 cm
Temple style	Flexible Spatula	Master Carton weight	16 kg
Nose Piece	Integral to lens	Master Packaging QTY	400 Units
Unit weight	25 Gram	Standards Met (Clear variants)	ANSI Z87.1-2020 AND IS 5983
Country of origin	India	Standards Met (Grey Variants)	ANSI Z87.1:2020, ANSI Z90.3:2018
		UV Protection	99.9%

Honeywell



SKU#	IESHCC10	IESAFC10	IESHCG10	IESAFG10
Fog Resistance Coating	No	Yes	No	Yes
Scratch Resistance Coating	Yes	Yes	Yes	Yes
Lens Tint	Clear	Clear	Grey	Grey
Temple/ Frame Tint	Matt Clear	Matt Clear	Matt Smoke Grey	Matt Smoke Grey
Marking ANSI	HON Z87+ U6	HON Z87+ U6	HON Z87+ U6L3	HON Z87+ U6L3
Marking IS	ISI Mark, IS 5983 V H	ISI Mark, IS 5983 V H		
Visible Light Transmittance	Yes	Yes	8.5 to 18%	8.5 to 18%
Lens	Zero Power, Non-Replaceable		Zero Power, Non-Replaceable	
Other Protection	High Velocity and Mass Impact		High Velocity and Mass Impact	
			Traffic Signal Recognition as per ANSI Z90.3:2018	
UV Protection	Yes	Yes	Yes	Yes



HONEYWELL A300 GOGGLE

TECHNICAL SPECIFICATIONS		TECHNICAL SPECIFICATIONS	
Lens overall width	185mm	Ind. poly-bag dimensions	28.4 x 15.2cm
Lens material	Polycarbonate	Primary Carton dimensions	30.5 x 17.8 x 10.2cm
Lens thickness	2.0 mm	Primary Carton weight	545 Gram
Head band strap	Adjustable Elastic Headband	Primary Packaging QTY	5 Units
Vents	Built-in 4 Indirect Vents to provide Airflow and Reduce Fog	Master Carton dimensions	61.5 x 36.8 x 54.6cm
Frame Material	PVC Compound	Master Carton weight	12.4 Kg
Unit weight	77 Gram	Master Packaging QTY	100 Units
Ind.Product dimensions	8.2 x 18.5 x 6.1cm	Standards passed	ANSI Z87.1-2020 AND IS 5983



SKU#	IEGHCC10	IEGAFC10
Anti Scratch	Yes	Yes
Fog resistance	No	Yes
Lens Tint	Clear	Clear
Frame Tint	Clear	Clear
Marking ANSI	HON Z87+ D3	HON Z87+ D3X
Marking IS	ISI Mark, IS 5983 V H S D G	ISI Mark, IS 5983 V H S D G
Lens	Zero Power, Non-Replaceable	Zero Power, Non-Replaceable
Visible Light Transmittance	Yes	Yes
Other Protection	High Velocity and Mass Impact	High Velocity and Mass Impact
	Droplets and Splash Hazard	Droplets and Splash Hazard
Coating	Scratch Resistant	Scratch and Fog Resistant
UV Protection	Only for Lens	Only for Lens

HONEYWELL A300 SERIES SAFETY EYEWEAR WITH YOU. FOR YOU.



For more information

Visit - www.honeywellsafety.com

or Contact us at:

hsp-India@honeywell.com

Contact us at

Honeywell International India Pvt Ltd

Unitech Trade Center, Sector 43,

Block-C, Sushant Lok,

Gurgaon 122002, Haryana, India

Honeywell