

WEBSAFE LIFEGUARD™ (WEBBING TYPE)

Technical Datasheet

The Websafe lifeguard™ is Horizontal temporary anchorage life line made up of 35 mm Polyester Webbing equipped with the Ratchet Tensioner that allows easy tensioning of the lifeline between two structures. Both the ends are provided with Steel Carabiners.

The integrated bag allows the excess webbing to be stored in there that is not being used. This can prevent damage from foot traffic, dirt and wear, thus improving the lifespan of the line. Connection to the line is made by attaching the Carabiner of a shock absorbing, or fall arrest lanyard directly to the line, again, reducing the potential for lost or damaged Component.

- There are many instances where a horizontal lifeline to ensure the safety of a user is the best practical option, but the time spent assembling and installing the system make it impractical to do so. What is needed is a quick means of installing the system so work is unaffected.
- The whole system is supplied in a bag, which is permanently attached to the assembly and also enables the user to easily carry the system with the help of comfortable shoulder hanging straps provided in the bag.
- Once fitted, you can easily put back the extra webbing not deployed along the length, into the Bag.



Overview

Key Features	Light Weight, Easy an quick installation, Came with Tensioner			
Recommended Industrial/ Use	• Agriculture	• Food services	• Mining	• Pharmaceutical
	• Chemical	• Forestry	• Municipal services	• Steel and metals
	• Construction	• Manufacturing	• Oil and gas	
Hazard Situation	Fall from height			
Regulation	Confirming to EN795 Class B			

Specifications

Webbing	35mm polyester webbing
Length	20 Meters
Number of users	2 Users maximum
Deflection	2 meters Maximum

Instruction for use

