

FALL ARRESTER BLOCK RETRO-GUARD (RG-FAB)

Technical Datasheet

The Retro-Guard, RG-FAB (Retractable Fall Arrester Block) is a personal protective equipment to protect against falls from a height and confirms to EN 360:2002. The fall arrester block provides protection from fall such as truck loading - unloading, Train top work, EOT cranes, pipe racks, confined space works and awkward work places where horizontal & Vertical safety required.



CE 0865
EN 360 : 2002

Features & Benefits

- High Impact load bearing polymer casing.
- Ergonomic Carry handle for ease of transportation.
- 4.8mm Stainless Steel Cable for added strength and safety.
- Can be use Horizontally.
- Steel Swivel Snap Hook with Fall Indicator.

Included



Carabiner



Tag Line

Technical Data

Anchorage Method	Forged Swivel Anchorage Eye
Casing	Polymer Casing
Wire rope	4.8 mm Stainless Steel (Min. Breaking Strength 15 KN)
Connectors & Hooks	Steel swivel snap hook (Min. Breaking Strength 23 KN) Steel Carabiner (Min. Breaking Strength 23 KN)
Load Capacity	140 kgs for vertical use. 100 kgs for horizontal use
Minimum Braking Strength	15 KN
Temperature Range	-30° C to +50° C
Certified to	EN 360:2002

Available Length



ESPAR0000035

Length - 06 meter | Weight - 4.4 Kgs.



ESPAR0000105

Length - 7.5 meter | Weight - 4.6 Kgs.



ESPAR0000106

Length - 10 meter | Weight - 4.7 Kgs.



ESPAR0000107

Length - 12 meter | Weight - 5.7 Kgs.



ESPAR0000108

Length - 15 meter | Weight - 6.8 Kgs.



ESPAR0000109

Length - 20 meter | Weight - 7.3 Kgs.

